DV-0101 DIGITAL VOLTMETERS DF-0101 DIGITAL FREQUENCY METERS DVF-0101 / DVF-0103 VOLT-FREQUENCY METERS 72x72 & 96x48mm SIZES TRUE RMS





DV-0101 Voltage





DF-0101 Frequency





DVF-0101 Voltage and Frequency





DVF-0103 3 Phase Voltage and Frequency



INTRODUCTION

These state-of-the-art panel meters are designed for accurate measurement of the AC RMS voltages and frequency in single-phase and three-phase systems. Although they are mainly used in electrical panels, these devices can also be integrated in many other applications.

Devices have separate inputs for supply and measurement with common neutral point.

Through front panel buttons, phase-to-phase (L1-L2, L2-L3, L3-L1) and phase-to-neutral (L1-N, L2-N, L3-N) voltages and frequency can be selected and read from the display. Automatic parameter scroll is also available

TECHNICAL SPECIFICATIONS

Power Supply Input: 170 - 275VAC

50 - 60Hz nominal (± 10%) Different AC/DC supply

values available.

Measurement Inputs:

10 - 300 V AC (Phase-Neutral) 20 - 520 V AC (Phase-Phase)

30 - 100 Hz

Accuracy: 0.5% + 1 digitPower Consumption: < 1.5W

Burden: < 0.1VA per phase Operating Temperature: -40°C;+70°C **Maximum Humidity:** 95% non-condensing. **Degree of Protection:** IP 54 (Front Panel)

IP 30 (Back panel)

Enclosure:

Non-flammable, ROHS compliant, high temperature ABS/PC (UL94-V0)

Installation:

Flush mounting with rear retaining brackets

Dimensions:

96x48 models: 102x54x41mm (WxHxD) **72x72 models:** 78x78x41mm (WxHxD)

Panel Cutout Dimensions:

96x48 models: 92x44mm 72x72 models: 68x68mm

Weight: 125 gr

EU Directives Conformity:

2006/95/EC (low voltage) 2004/108/EC (EMC)

Norms of reference:

EN 61010 (safety requirements) EN 61326 (EMC requirements)


PACKAGING INFORMATION

Pieces per Package: 24 Pcs


Package Size: 280 x 170 x 215mm (LxWxH)

Package Weight: 3.2 kg

CONNECTION DIAGRAM



DV-0101 DF-0101 **DVF-101**



MOUNTING TOLERANCES

